



ZB7306-xxxx | EtherCAT P cable, no total screen, PUR, drag chain suitable, 3G2.5 mm² + 2 x 1.5 mm² +(1 x 4 x AWG22), black with red stripe, OD = 11.9 (±0.4 mm)

Electrical data	
Operating voltage	≤ 1000 V AC
Mutual capacitance wire/wire (Ethernet)	nom. 55 nF/km
Attenuation of shielding	≥ 40 dB (30...100 MHz)
Insulation resistance	≥ 500 MΩ * km (DIN EN 50395)
Mutual capacitance	AWG 22: nom. 55 nF/km
Wire resistance (power)	2.5 mm ² : ≤ 8.3 Ω/km, 1.5 mm ² : ≤ 14.0 Ω/km
Wire resistance (Ethernet)	≤ 58.0 Ω/km according to DIN EN 50395
Characteristic impedance (Ethernet)	100 Ω ±5 Ω (100 MHz)
Dielectric strength wire/wire (power)	4 kV 50 Hz 1 min.
Dielectric strength wire/shield (power)	4 kV 50 Hz 1 min.
Dielectric strength wire/wire (Ethernet)	4 kV 50 Hz 1 min.
Dielectric strength wire/shield (Ethernet)	4 kV 50 Hz 1 min.
Test voltage	4000 V, 50 Hz, 1 min. (wire/wire and wire/screen)
Mechanical data	
Cable structure (Ethernet)	star quad
Conductor construction (Ethernet)	7-strand
Cross section (power)	3 x 2.5 mm ² (approx. AWG14) + 2 x 1.5 mm ² (approx. AWG16)
Cross section (Ethernet)	1 x 4 x 0.34 mm ² (AWG 22)
Min. bending radius, moved	7 x outer cable diameter
Min. bending radius, fixed installation	4 x outer cable diameter
Weight	210 kg/km (140.7 lb/1000 ft)
Outer cable diameter	11.9 mm ± 0.4 mm (0.469" ± 0.0157")
Conductor material (power)	copper bare
Conductor material (Ethernet)	bare copper
Shielding	braiding of tinned copper wires, metallised plastic fleece, aluminium-clad foil

Optical covering factor of shielding (Ethernet)	≥ 85 %
Optical covering factor of shielding (total)	no
Use	drag-chain suitable
Max. acceleration	30 m/s ²
Max. speed	4 m/s
Max. travel distance	20 m
Max. number of cycles	5 million
Wall thickness of wire insulation (power)	0.45 mm
Jacket colour	black (similar to RAL 9005) with red stripe (similar to RAL 3020)
Material jacket	PUR (polyurethane)
Wire colour code	yellow, orange, white, blue (Ethernet), black, red (1.5 mm ²), green/yellow, brown, blue (2.5 mm ²)
Wire insulation material	PO (Polyolefine)
Printing on the jacket	xxxx m Beckhoff Automation GmbH & Co. KG - Germany - EtherCAT P ZB7306 3 G 2,5 + 2 x 1,5 + (4xAWG22)/C E63216 c us AWM 21223 AWM I/II A/B 80°C 600V FT1 RoHS MM/JJ (MM/JJ= month of production/year of production) outer diameter: (11.9 ± 0.4) mm
Printing colour	white
Torsion angle in °/m	max. ± 30 °/m
Environmental data	
Operation temperature range, moved	-20...+60 °C, -4...+140 °F
Operation temperature range, fixed installation	-40...+90 °C, -40...+194 °F
UV resistance	yes
Oil resistance	yes
Acid, lye and solvent resistance	depends on medium, concentration, temperature and duration
LABS-free	yes
Flame-retardant	according to UL 758 (cUL-FT1)
Halogen-free	yes
Silicone-free	yes
Approvals	cULus AWM Style 21223 80°C 600V

Attenuation								
Max. insertion loss								
Frequency [MHz]	1	4	10	16	20	31.25	62.5	100
[db/100 m]	-	4.2	6.8	8.6	9.7	12.3	18.0	23.6
[db/100 ft]	-	1.3	2.1	2.6	3	3.7	5.5	7.2
Min. near-end crosstalk attenuation								
Frequency [MHz]	1	4	10	16	20	31.25	62.5	100
[db/100 m]	65.3	56.3	50.3	47.2	45.8	42.9	38.4	35.3
[db/100 ft]	19.9	17.2	15.3	14.4	14	13.1	11.7	10.8

Notes

- The following length tolerances apply: 2-3 %
- Illustrations similar

Ordering information	Length
ZB7306-xxxx	sold by the metre

Beckhoff®, TwinCAT®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, Safety over EtherCAT®, TwinSAFE®, XFC®, XTS® and XPlanar® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 02/2021

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.