

ZB9052 | Power/sensor cable, PUR, 4 x 0.5 mm², capable of torsion, black

Electrical data	
Rated voltage	300 V
Insulation resistance	≥ 500 MΩ/km
Wire resistance (signal/24V)	ca. 39 Ω/km
Test voltage	≥ 2000 V
Mechanical data	
Conductor construction (signal/24V)	28 x 0.15 mm, conductor class 6 according to DIN VDE 0295
Cross section	4 x 0.5 mm ² (AWG20)
Min. bending radius, moved	7.5 x outer cable diameter
Min. bending radius, fixed installation	4 x outer cable diameter
Weight	53.6 kg/km (36.02 lb/1000 ft)
Outer cable diameter	6.0 mm ± 0.2 mm ("0.23622 ± 0.0079")
Conductor material (signal/24V)	copper bare
Shielding	no
Use	robotic- and drag chain suitable
Max. acceleration	5 m/s ²
Max. speed	3.3 m/s
Max. travel distance	100 m
Max. number of cycles	10 million
Jacket colour	black
Material jacket	PUR (polyurethane)
Material jacket, further characteristics of	weld-spatter resistant, low adhesion
Wire colour code	white, blue, black, brown
Wire insulation material	TPE (thermoplastic elastomer)
Printing on the jacket	XXXXM Beckhoff Automation GmbH & Co. KG -Germany-Sensor ZB9052 - 4x0,5mm ² E170315 cRUus AWM STYLE 20233 AWM I/II A/B 80°C 300V FT1
Printing colour	white
Torsion angle in °/m	max. ± 360°/m
Torsion speed	15 cycle/min.
Number of torsion cycles	10 million
Claimed torsion length	2 m
Environmental data	
Operation temperature range, moved	-30 °C... +105 °C, -22 °F...+221 °F, UL: up to +80 °C (+176 °F)
Operation temperature range, fixed installation	-40...+105 °C, -40...+221 °F
Oil resistance	very good oil and chemical resistance
LABS-free	yes
Flame-retardant	according to IEC 60332-1
Halogen-free	yes
Silicone-free	yes

Notes

- The following length tolerances apply: 2-3 %
- Illustrations similar

Ordering information	Length
ZB9052	sold by the metre

Beckhoff®, TwinCAT®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, Safety over EtherCAT®, TwinSAFE®, XFC®, XTS® and XPlana® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 02/2021

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.