

PR152017

28th November 2017

I/O

Sivu 1 / 3

Highly compact electronic overcurrent protection in 12 mm EtherCAT Terminals

Järjestelmään integroitu ylivirtasuojaus EtherCAT-I/O-järjestelmässä

In the new EL922x EtherCAT Terminal series, Beckhoff has directly integrated electronic overcurrent protection to safeguard 24 V DC system components in the highly compact EtherCAT I/O system. In comparison with currently available protection devices, costs and space requirements in control cabinets can be reduced without having to use a conventional, inflexible stand-alone system. With an extended range of settings and process data options, the EL9227 EtherCAT Terminals meet the most diverse requirements and enable transparent system monitoring.

The EL922x Terminal series for overcurrent protection is designed for 24 V DC operation and includes 19 different EtherCAT Terminals. There are 1- and 2-channel versions for various current loads up to a maximum of 10 A. Furthermore, the wide range of terminals is divided into:

- EL9221 and EL9222 Terminals with standard functionality such as rated current, which can be parameterised not only using TwinCAT System Manager software, but also conveniently with an LED button, and
- EL9227-xxxx Terminals with extended functionality that can be parameterised in the TwinCAT System Manager, such as the selection of a characteristic curve, preliminary warning threshold, undervoltage signal, feedback cut-off, event logging and a password-protected software seal.

PR152017

28th November 2017

I/O

Sivu 2 / 3

System-integrated overcurrent protection offers numerous practical benefits for users. Wiring effort is reduced, since the feed into adjacent I/O terminals is achieved automatically by simply plugging in the terminal. In addition, control cabinets benefit from space and cost savings because additional coupling hardware and other digital I/O or power feeding products are no longer required. Furthermore, numerous types of process data can be accessed via EtherCAT, for example utilisation rate, load current, input/output current, undervoltage/overvoltage and feedback. This enables transparent system monitoring, minimised downtime, simplified troubleshooting and a comprehensive overview of plant history.

→ www.beckhoff.fi/el922x

PR152017

28th November 2017

I/O

Sivu 3 / 3

Lehdistökuva:



Kuvateksti:

Measuring just 12 mm wide, the new EL922x series EtherCAT Terminals from Beckhoff provide overcurrent protection directly in the EtherCAT system.

Lataa kuva:

download.beckhoff.com/download/press/2017/pictures/pr152017_Beckhoff.zip

Lukijakysymykset aiheesta voi lähettää osoitteeseen:

Beckhoff Automation Oy

Hakakalliontie 2, 05460 Hyvinkää

Puhelin: + 358 (0) 20 7423 800

Sähköposti: info@beckhoff.fi, www.beckhoff.fi